

Product: Integrated LED - Cylinder

Product Code: MLILCYL30



Warranty 36 months from shipment



Key Features:

Voltage: 120-277V AC
Power: 10Watt, 15Watt, 20Watt
Dimmable: Yes, TRIAC Dimming
Light Projection: Downward
LED Working Hours: 30,000

Lighting Performance:

Dimensions	Power	Luminous Efficacy	LED Colour Temperature	CRI	Lumen Output
3" (Dia) X 8" (H)	10W	60-70 Lumens/watt	2700-6000K	>80	600 Lumens
4" (Dia) X 8" (H)	15W	60-70 Lumens/watt	2700-6000K	>80	900 Lumens
6" (Dia) X 10" (H)	20W	60-70 Lumens/watt	2700-6000K	>80	1200 Lumens

Standard finishes



Dimensions (inch):

3 (Dia) X 8 (H) – 10W 4 (Dia) X 8 (H) – 15W 6 (Dia) X 10 (H) – 20W Hanging Stem: 12"

Canopy Dimensions (inch):

Diameter: 6"
Height: 1"
Width: N/A
Extension: N/A

Type:

Integrated LED Cylinder

Usage:

Indoor Dry Location

Material:


Metal and Acrylic Diffuser

Mounting:

Ceiling - Pendant Mount

Finish: Oil Rubbed Bronze (ORB), Brushed Nickel (BN), Chrome (CH), Brass (BR) Powder Coated Finish: White (WH), Black (BK), Gray (GR) ** Custom finish as requested

Powder coated finishes



Copyright (2025-2026) Meomi Lighting https://meomilighting.com

Light Temperature Guide:



Shade / Glass / Diffuser Details:

	Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
1	Diffuser	Acrylic											

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual										
Master Pack										
Shipping Master										
NJ Pallet										
NV Pallet										

Project Name:		Notes:
LED Color Temperature:	2700-6000K	
Body Finishes:		
Acrylic Finishes:		

Disclaimer:

- Product details are subject to change without prior notice
 Please contact nearest Meomi Lighting team/representative for all engineered solutions requirements
- Products may vary from the picture(s) provided in this data sheet