MEOMI LIGHTING

Product: Integrated LED – Track Light
Product Code: MLILTL15

Dimensions (inch):

Diameter:	**2.17"/2.64"/3.27"/3.74"**
Height:	**5.5"/5.91"/6.6"/7.1"**
Length:	**3.66"/4.33"/4.53"/5.24"**
Depth:	**N/A**

Canopy Dimensions (inch):

Diameter:	**N/A**
Height:	**N/A**
Width:	**N/A**
Extension:	**N/A**

Type:
Integrated LED – Track Light

Usage:
Indoor Dry Location

Material:
Metal and Acrylic Diffuser

Mounting:
Ceiling/Track/Wall

Warranty
36 months from shipment

Certification

cETLus Listed Intertek

Key Features:
- Light Source: LED
- Voltage: 120VAC
- Frequency: 60Hz
- Dimmable: Yes, TRIAC Dimming
- Beam angle: 15º/25º/36º/55º
- Power Factor: >0.98
- LED Colour Temperature: 2700/3000/3500/4000/5000K
- 3CCT Tunable: 3000/4000/5000K

Lighting Performance:

Dimensions (inch)	Power	LED Working Hours	Luminous Efficacy	CRI	Lumen Output
2.17 (Dia) X 3.66 (L) X 5.5 (H)	7W	30,000	110 Lumens/watt	>83Ra/95Ra	770 Lumens
2.64 (Dia) X 4.33 (L) X 5.91 (H)	10W		110 Lumens/watt		1100 Lumens
3.27 (Dia) X 4.53 (L) X 6.6 (H)	15W		106.67 Lumens/watt		1600 Lumens
	20W		107.5 Lumens/watt		2150 Lumens
3.74 (Dia) X 5.24 (L) X 7.1 (H)	25W		104 Lumens/watt		2600 Lumens
	30W		106.67 Lumens/watt		3200 Lumens

Powder Coated Finish: White (WH), Black (BK), Gray (GR)
** Custom finish as requested

Powder coated finishes

Black (BK) Gray (GR) White (WH)

Light Temperature Guide:

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Diffuser	Acrylic											

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual										
Master Pack										
Shipping Master										
NJ Pallet										
NV Pallet										

		Notes:
Project Name:		
LED Color Temperature:	2700-5000K	
Body Finishes:		
Acrylic Finishes:		

Disclaimer:
• Product details are subject to change without prior notice
• Please contact nearest Meomi Lighting team/representative for all engineered solutions requirements
• Products may vary from the picture(s) provided in this data sheet